

Navy Case No. 82,918

ARRANGEMENT AND CONSTRUCTION OF AN ELEMENT BUNDLING MODULE

[0001] The present invention relates in general to a module enclosing bundled elements in different installations.

BACKGROUND OF THE INVENTION

[0002] The processing of contaminate laden fluid such as oily wastewater collected within marine vessels, by passage through ultra-filtration membranes for fluid cleansing purposes is generally known in the art, involving a module containing one or more of such filtration membranes having pores through which the oily wastewater percolates during passage through a tubular module housing. Various problems arise with respect to providing a suitable arrangement of apparatus for the performance of such wastewater cleansing operation in such installations on board marine vessels, imposing different handling requirements and dimensional restrictions. It is therefore an important object of the present invention to provide a more efficient and less costly arrangement of bundled elements such as filter membranes within modules for cleansing of contaminate laden fluids such as oily wastewater by filtration through the filter membranes.

SUMMARY OF THE INVENTION

[0003] In accordance with the present invention, a plurality of elongated elements of a desired number are disposed in parallel spaced relation to each other within a single tubular housing shell of a module. Where such elongated elements are filter membranes, ultra-filtration processing of a contaminate laden fluid is performed within such module housing to discharge a contaminate cleansed portion of the fluid from a drain. Positioning of and spacing between elongated elements for most compatible and efficient integration and processing is effected by

09829870-061301

1 anchoring of opposite axial end portions of such elements within the module housing to form a
2 bundle enclosed within a percolation chamber from which the filtration cleansed fluid portion is
3 drained. Sealing of such percolation chamber and positioning of the filter elements therein is
4 effected by use of a pair of axially spaced seal rings seating annular seals in contact with the
5 internal cylindrical surface of the module shell housing. Each of such seal rings retains an epoxy
6 resin holding disc within which the axial end portions of the filter membrane elements are held
7 positioned in parallel spaced relation to each other. The spacings between such filter elements are
8 maintained throughout within the percolation chamber between the filter holding discs by pairs of
9 rubber spacer o-rings located on the filter elements adjacent to the filter holding discs and
10 midway therebetween. The filter holding discs are formed from bodies of epoxy resin
11 respectively cured in-situ within the seal rings with the filter elements positioned therein before
12 assembly within the filtration module housing.
13

14 [0004] As a result of the foregoing described constructional arrangement and associated
15 fabrication procedure, processing efficiency in the case of filtration is maximized by increasing
16 surface area exposure of the filter elements within a single module housing, minimizing and
17 maintaining spacing between the filter elements positioned therein and sealing the percolation
18 chamber therein. Energy losses as well as leakage are thereby reduced and fabrication costs
19 minimized by limiting close tolerance to the seal rings. Further, the foregoing benefits may be
20 applied to modules of different dimensions, while replacement of parts may be limited to the filter
21 element holding discs formed by in-situ curing of the epoxy resin, should fabrication defects
22 occur, so as to avoid replacement of the filter membrane elements. The arrangement of the
23 present invention while applicable to other installations such as heat exchange tubes bundled
24 within a module shell, is applied to bundling and sealing of filtration membrane elements within
25
26
27
28

1 the module shell in order to maximize surface area convection. The number of such elements for
2 a given shell size is thereby increased and the cost of sealing individual elements is lowered.

3 BRIEF DESCRIPTION OF DRAWING

4 [0005] A more complete appreciation of the invention and many of its attendant
5 advantages will be readily appreciated as the same becomes better understood by reference to the
6 following detailed description when considered in connection with the accompanying drawing
7 wherein:
8

9 [0006] FIG. 1 is a perspective view of a filtration module constructed in accordance with
10 one embodiment of the present invention;

11 [0007] FIG. 2 is a partial longitudinal section view of the module shown in FIG. 1, taken
12 substantially through a plane indicated by section line 2-2;

13 [0008] FIGS. 3 and 4 are partial transverse section views taken substantially through
14 planes indicated by section lines 3-3 and 4-4 in FIG. 2;

15 [0009] FIG. 3A is a partial section view similar to that of FIG. 3, showing another
16 embodiment; and
17

18 [0010] FIG. 5 is a partial side section view of an arrangement of filter elements within a
19 body of epoxy resin retained within a seal ring during curing under clamping pressures, before
20 fabrication completion and assembly of the module shown in FIGS. 1-4.

21 DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

22 [0011] Referring to the drawing in detail, FIG. 1 illustrates a module 10 having an outer
23 cylindrical housing 12 extending longitudinally between an axial inlet end 14 thereof and its other
24 axial outlet end 16. Such module housing 12 is made of a rigid material having suitable
25 properties such as a metal or plastic having fluid confining and contaminate resisting properties.
26
27
28

1 In such case a contamination laden fluid such as oily wastewater enters at the inlet end 14 and is
2 processed so as to separate a contaminate cleansed fluid portion before exiting from the outlet end
3 16. Such separated cleansed fluid portion is discharged from a drain 18 located on the housing
4 12, spaced between the outlet end 16 and the inlet end 14.

5 [0012] Referring now to FIGS. 2, 3 and 4, ultra-filtration processing within the module
6 housing 12 is performed during passage of the oily wastewater under pressure between the inlet
7 and outlet ends 14 and 16 by a plurality (three or more) of elongated elements 20 in the form of
8 filter membranes. Such separation of water from contaminants occurs as a result of oily
9 bilgewater percolation laterally within a sealed chamber so as to gravitationally collect therefrom
10 the contaminate cleansed portion for discharge therebelow through the drain 18. The elements 20
11 made of membrane material having pores through which percolation of the bilgewater occurs, are
12 positioned in generally parallel spaced relation to each other by a pair of surrounding rigid
13 annular seal rings 22 within which holding discs 24 molded from epoxy resin are retained for
14 anchoring therein the axial ends of the elements 20. Each of the seal rings 22 is externally
15 grooved for retention of a pair of annular rubber seals 26 in sealing contact with the internal
16 surface of the tubular module housing 12. Radial sealing is thereby established within the module
17 housing 12 by the seal rings 22, with the seals 26 and the filter holding discs 24 to seal a
18 percolation chamber 25 within which ultra-filtration is performed and to avoid mixing between
19 the contaminate cleansed fluid with the contaminate laden fluid during passage through the
20 housing 12.

21 [0013] The elements 20 are maintained in parallel spaced relation to each other between
22 their axial ends by o-ring spacers 28 as shown in FIG. 2. Pairs of such spacers 28 are disposed in
23 close spaced relation to the epoxy resin molded discs 24, in order to sustain spacing throughout
24
25
26
27
28

1 between sufficiently stiffened filter elements 20. Positioning of such elements 20 that are
2 circular in cross-section within a bundle formation in the module housing 12 are also thereby
3 effected by the spacers 28 as shown in FIG. 3. FIG. 3A illustrates a modification, wherein
4 comparable elements 20' of hexagonal cross-section are maintained in spaced relation to each
5 other by similar spacers 28'.

6
7 [0014] The molded epoxy resin discs 24, holding the processing elements 20 in position
8 within the single module 10 together with its seal rings 22, provides a sealing action between the
9 module housing 12 and the bundled elements and between the individual elements so as to
10 separate a contaminant-laden fluid, such as bilgewater, from a cleansed portion discharged
11 through the drain 18 in the case of processing elements that are filter membranes. Dimensional
12 compatibility is thereby also provided so as to accommodate integration of multiple types and
13 different numbers of bundled elements. Such integration of the bundled elements 20 within with
14 the module 10 as a single component for example, is facilitated by an associated fabrication
15 procedure as hereinafter outlined by reference to FIG. 5.

16
17 [0015] As shown in FIG. 5, a plurality of the elements 20 to be bundled in close parallel
18 spaced relation to each other are disposed in their desired relative positions within a body of
19 uncured epoxy resin from which one of the holding discs 24 is separately formed within one of
20 the seal rings 22 before assembly within a module 10. The epoxy resin in the uncured fluent state
21 will fill all spaces between the axial end portions of the elements 20 to be bounded within the
22 inner diameter of the annular seal ring 22. Positioning of the filter elements 20 during the latter
23 described stage of the fabrication procedure, before molding of the holding discs 24, is
24 established by clamping between fixedly spaced rigid plates 30 and 32 on which resilient material
25 layers 34 and 36 are respectively disposed. To facilitate molding, a thin mold release film 38 is
26
27
28

1 placed on the resilient layer 34 underlying the lower ends of the elements 20 within the uncured
2 body of epoxy resin retained within the seal ring 24 under pressure as denoted by arrow 40 and a
3 clamping pressure on the plate 32 as denoted by arrow 42. The thickness of the holding discs 24
4 is determined by the height of the seal ring 22. When one of such discs 24 is so formed upon full
5 curing of the epoxy resin after 24 hours for example, the element bundle as shown in FIG. 5 is
6 then rotated 180° and the same fabrication procedure is repeated to form another holding disc 24
7 at the other ends of the elements 20 to complete bundling of the elements before transfer to the
8 module 10 for assembly therein.

9
10 [0016] The foregoing described arrangement associated with the module 10 may be
11 utilized to sealingly bundle elongated elements, other than filter membranes, in different
12 installations. For example, such elongated elements to be bundled may be electrical cables,
13 optic cables, pneumatic hoses/tubes, etc.

14
15 [0017] Obviously, other modifications and variations of the present invention may be
16 possible in light of the foregoing teachings. It is therefore to be understood that within the scope
17 of the appended claims the invention may be practiced otherwise than as specifically described.

18 What is claimed is:
19
20
21
22
23
24
25
26
27
28